





TWO POST FLEXMETRIE 12,000 LB CAPACITY



MORE SPEED = MORE PRODUCTIVITY

DASH XII - FLEXMETRIC

LOADING + 35 SECONDS RISE TIME

A Truck Lift Designed With Cars In Mind

- Flexmetric Or Symmetric 12,000 Lb. 2 Post
- Versatile For Both Cars & Light Trucks
- Two Position Adjustable Overhead
- Gear Lock Arm Restraints
- Reinforced More Stable Column Structure
- Durable Powder Coat Finish In Red Or Blue
- Premium North American Power Unit
- Rubber Door Bumpers & Pump Mounts
- Stacking Adapters Provide Up To 84" Of Lift Height

CAPACITY 12,000 LBS

Model Number TLS212MRx1 TLS212SRx1



• STABILITY AND SMOOTH OPERATION

Heavy duty columns with close fitting carriages for smooth and secure vehicle lifting

• GREATER FLEXIBILITY WITH AN OPTIMUM HEIGHT & WIDTH

159 inches installation height - 137 inches wide

• STAYS LEVEL ALL THE TIME

Twin hydraulic cylinders and cable equalization for dependable performance

• QUALITY POWER UNIT WITH FLEXIBLE MOUNTING

Power pack can be mounted on driver or passenger side for individual application

• LOWER MAINTENANCE COST AND DOWN TIME

3 inch steel cable pulleys for durability and low maintenance

WORK SAFELY AT MORE WORKING HEIGHTS

Mechanical safety locks automatically engage at 16 different operating heights

• DEPENDABLE USER FRIENDLY CONTROLS

Single point safety lock release and two-hand lift lowering contribute to safe operation

• FASTER SET UP INCREASES PRODUCTIVITY

Stack pad lift system with standard $1\frac{1}{2}$ ", 3" and 6" height extension adapters

• ELIMINATES CAR DOOR DAMAGE

Bumper guards on both columns protect vehicle doors from damage

• ENERGY EFFICIENT POWER SUPPLY

North American made power unit 230V - 1 phase -60 Hz - 20 Amp power required (optional 230V -3 phase - 60 Hz available)

TWO POST FEATURES	4TP212NSx1	4TP212SSx1	
ALI/ETL Certified	yes		
Flexmetric Dual Purpose Lifting	yes	no	
Clear Floor Design	yes		
Cable Equalization	yes		
Standard Height Model	yes		
Extended Height Model	yes		
Standard Width Model	yes		
Door Bumper Guards	yes		
Structural Warranty	2 years		
Hydraulic Parts Warranty	2 years		
Others Parts Warranty	2 years		
Accessories Warranty	90 days		
Labor Warranty	1 year		
Optional Blue Paint	yes		
Optional 3 Phase Power	yes		

SPECIFICATIONS	4TP212NSx1	4TP212SSx1
Capacity	12,000 lbs.	
Overall Width	137"	
Width Between Columns	1091/2"	
Drive Thru Width	94″	
Overall Height	159″	
Under Bar Clearance	153"	
Lowered Height - Standard Lift Pad	4 ^{1/2} "	
Raised Height - Standard Lift Pad	75″	
Raised Height With Adapter	84" w/3" and 6" adapter	
Front Arm Length	28" to 40 ^{1/2} "	
Rear Arm Length	39" to 58"	
Lift Time	45 seconds	
Power Requirement	230V - 60Hz - 1Ph - 20 Amp	
Shipping Weight	2,300 lbs.	

Available Accessories





Height Adapters Outer Arm Adapter



Air - Electric Station





