



TLS 4 POST LIFT OPEN FRONT

14,000 lbs. Capacity

- Open Front Alignment model
- 20" wide runways with checker plate surface adds to strength, vehicle tracking and service ca
- 8½" lowered height facilitates drive on of low profile vehicles
- Powerpack operator controls on rear driver side
- No vehicle door damage with hidden cylinder under the runway
- Adjustable safety lock ladders level the runways and compensate for uneven floors
 - Model Number TLS414ALORx1 TLS414ALOXx1
- 74" slip plates and multi position turnplate pockets handle **TLS414FDOXx1 TLS414FDORx1** short and long vehicles
- Add optional rolling air/hydraulic jacks for the ultimate in complete vehicle servicing
- 230V 1 phase 60 Hz 20 Amp power required (optional 230V - 3 ph powerpack available)

Available Accessories



Rolling Air Hydraulic Jacks TLSRJ7



Stainless Steel Turnplates
TLSSSTP

4 POST LIFTS	TLS414ALORx1 - TLS414ALOXx1 TLS414FDOXx1 - TLS414FDORx1
Capacity	14,000 lbs
Overall Length Standard Model	256"
Overall Length Extended Model	292"
Deck Length Standard Model	205″
Deck Length Extended Model	242"
Overall Width Front	139"
Overall Width Rear	137"
Deck Width	20"
Raised Height	721/2"
Minimum 4-Wheel Alignment Wheelbase	86"
Maximum 4-Wheel Alignment Wheelbase	164"
Maximum 2-Wheel Alignment Standard Model	178"
Maximum 2-Wheel Alignment Extended Model	214"
Maximum Service Wheelbase Standard Model	186"
Maximum Service Wheelbase Extended Model	222"
Lift Time	58 seconds
Power Requirements	230 V AC - 60Hz - 1Ph - 20 Amp
Shipping Weight	3,395 lbs





