




## TLS FOUR POST PLATFORM LIFT

## 19,000 lbs. Capacity

- GREATER FLEXIBILITY WITH MORE MODELS TO CHOOSE FROM Closed Front Alignment or Flat Deck models standard or extended length.
- MORE VERSATILE ACCOMMODATES BOTH TRUCKS & CARS 23" wide runways easily handle cars and light trucks with dual wheels.
- SMOOTH OPERATION & LOWER MAINTENANCE COST Solid 9" Pulleys and 9/16" DIA Steel cable.
- EASIER ACCESSIBILITY FOR LOWERED VEHICLE Lowered height facilitates drive on of low profile vehicles.
- SAFE AND RELIABLE SAFETY SYSTEM
   Air Operated Stainless Steel safety
   lock releases in each post and Hydraulic Velocity Fuses
- ELIMINATES CAR DOOR DAMAGE
   No vehicle door damage with hidden cylinder under the runway.
- ADAPTS TO ALL FLOORS FOR A LESS COSTINSTALLATION Adjustable safety lock ladders level the runways and compensate for uneven floors.
- GREATER SELECTION OF SPECIALTY OPTIONS
   Add optional rolling air/hydraulic jacks and heavy duty turn plates for the ultimate in complete vehicle servicing.
- ENERGY EFFICIENT POWER SUPPLY 230V - 1 phase - 60 Hz - 20 Amp power required. (optional 230V - 3 phase power pack available)



PLATFORM LIFT FEATURES	TLS419ALCRx1 - TLS419ALCXx1 TLS419FDCXx1 - TLS419FDCRx1
ALI/ETL Certfied	yes
23" Wide Dual Wheel Compatible	yes
Built in Front Radius Plate Pockets & Rear Slip Plates	yes
Image Aligner Compatible	yes
Rear Slip Plates Maintenance Free with 3/4" Chromed Bearings & Open Deck Surface	yes
Double Bake Bake Powder Coat Finish	yes
Machined Steel 9" Pulleys & 9/16" Pre-stressed Cable	yes
Low Approach Angle with 10" Lowered Height	yes
Fully Adjustable Locking Rack	yes
Adjustable Locking Ladders in Each Column	yes
Premium North American Made Power Unit	yes
Air Regulator with Water Trap/Oiler	yes
Available for Wheel Bases up to 208"	yes
Raised Height of 74"	yes
Parts Warranty	2 years
Labor Warranty	1 year
Hydraulics Warranty	2 years
Structural Warranty	2 years
Accessory Warranty	90 days
Optional 3 Phase Power	yes

SPECIFICATIONS	TLS419ALCR×1 - TLS419ALCX×1 TLS419FDCX×1 - TLS419FDCR×1
Capacity	19,000 lb.
Overall Length Extended Model	301"
Overall Length Standard Model	274″
Deck Length Extended Model	237"
Deck Length Standard Model	210″
Overall Width	150″
Deck Width	23"
Lowered Height	10"
Raised Height	74"
Min. 4 Wheel Align. WB	91"
Max.4 Wheel Align. WB	161"
Max. 2 Wheel Align. WB	205" or 178"
Max. Service WB	213" or 186"
Lift Time	100 seconds
Power Requirement	230V - 60Hz - 1 Ph - 25 Amp
Shipping Weight	5,000 lb.

## **Available Accessories & Options**



Rolling Air/ Hydraulic Jacks TLSJ9000



Stainless Steel Turnplates TLSSSTP



Built in Tire Inflation Hoses



Stainless Steel Rear Slip Plates



Runway Step Platforms



LED Runway Lighting

